



FGG21705

12Volt 17Ah

Specifications

Nominal Voltage(V) **12V**

Nominal Capacity

20 hour rate	(0.85A	to	10.50V)	17Ah
5 hour rate	(2.89A	to	10.20V)	14.45Ah
1 hour rate	(9.35A	to	9.60V)	9.35Ah
3 C	(17A	to	9.60V)	9.07Ah

Weight **Approx. 6.28kg(13.82Lbs.)**

Internal Resistance (at 1KHz) **Approx. 10 mΩ**

Maximum Discharge Current for 5 seconds: **255A**

Charging Methods at 25 (77)

Cycle use:

Charging Voltage **13.8 to 14.4V**

Coefficient -5.0mv/ /cell

Maximum Charging Current : **5.1A**

Standby use:

Float Charging Voltage **13.50 to 13.80V**

Coefficient -3.0mv/ /cell

Operating Temperature Range

Charge **-15 (5) to 40 (104)**

Discharge **-15 (5) to 50 (122)**

Storage **-15 (5) to 40 (104)**

Charge Retention (shelf life) at 20 (68)

1 month **92%**

3 month **90%**

6 month **80%**

Case Material **ABS**

(UL94 HB flame retardant)

Terminal **F6**

Description of torque value of hard ware for the terminals:


Recommended torque value **M5: 2.94 N-m (30kg-cm)**

Maximum allowable torque value **M5: 4.90 N-m (50kg-cm)**




Dimensions


mm(inch)




(v) Discharge Time VS. Discharge Current (25)




Effect of Temperature on Capacity 25 (77)



Capacity Retention Characteristic



Trickle (or float) Service Life



Cycle Service Life

